

# **Overview**

# Cable pulley 52/4 mm with holder for lifting / lowering heater - PU = 1 pcs

**Product number:** 04400094-1



## **Options**

### PU (Pcs)

1

25



# **Description**

Thanks to two ball bearings, **the 52 mm pulley** is guided particularly securely on the axle and has a high level of stability under shear loads.

### Created at 27.10.2025.



Fiberlane LLC - 9254 Richmond Road - 18013

Bangor, PA

email:

Tel.: +1 610 498 447 4


Fax.: +1 610 498 2602

info(at)fiberlanellc.com

The galvanised steel bracket can be attached to your construction with an **M8 screw**. The retaining bracket can also be detached from the pulley to make installation **as easy as possible**, even in installation situations that are difficult to access.



- Impact resistant pulley
- Galvanised steel bracket
- Two ball bearings
- Load capacity: up to 280 kg
- Made in Germany



Outer diameter: 52 mmTotal height: 77,75 mm




Fiberlane LLC - 9254 Richmond Road - 18013 Bangor, PA

hmond Road - 18013 Fax.: +1 610 498 2602

Tel.: +1 610 498 447 4

email:

info(at)fiberlanellc.com



• Total width: 20 mm

Rope diameter: up to Ø 8 mm
Fastening with M8 screw / bolt