Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Overview

Cable drum for 63 mm (2.48 in) tube - type III - Motion range 570 cm (224 in)

Product number: 21198114-1



Image

Options

Version

34 mm / 1" | 50,05 mm / 1,5 " | 60,6 mm / 2" | 63 mm

PU (Pcs)

1 | 12

Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Description

This grooved cable drum ensures friction free, well-ordered winding and therefore a smooth movement of driving cable in shading systems .

Two-halves model of the drum makes it possible to fasten it onto drive shaft subsequently. The two halves are connected quick and easy with a hose clamp and then installed onto the drive shaft with a headless screw.

The cable drum is made of high-impact resistant plastic, that is friendly to cables and therefore increases their durability.

Can be used with cords with a diameter up to 3 mm
For 63 mm drive shafts
Capacity of cable drum: up to 5,70 m

All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.