Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Overview

Cable drum 2" - type III - motion range 570 cm (224 in)

Product number: 21198105-1



Image

Options

Version

34 mm / 1" | 50,05 mm / 1,5 " | 60,6 mm / 2" | 63 mm

PU (Pcs)

1 | 12

Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Description

- **Application area:** Uniform winding of wire ropes in shading systems
- **Material:** Impact-resistant plastic for high durability
- **Capacity:** Winding length 570 cm
- **Installation:** Retrofittable onto the drive shaft
- **Special feature:** Two-part design with hose clamp connection

The **Cable drum 2″ – Type III** enables structured winding of wire ropes via pre-grooved plastic, ensuring smooth cable movement within the shading system. Friction between wound wires and ropes is effectively prevented.

Thanks to its two-part design, the cable drum can be retrofitted onto the drive shaft. The two halves are joined using a hose clamp, while the drum is secured to the shaft with a set screw.

The impact-resistant plastic protects the wire rope and extends its service life. Suitable for wire ropes with a diameter of up to 3 mm.

All prices excl. VAT plus shipping costs and possible delivery charges, if not stated otherwise.