Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Overview

Cable drum for 63 mm (2.48 in) tube - type III - Motion range 570 cm (224 in) - PU = 12 pcs

Product number: 21198114



Image

Options

Version

34 mm / 1" | 50,05 mm / 1,5 " | 60,6 mm / 2" | 63 mm

PU (Pcs)

1 | 12

Fiberlane LLC.
9254 Richmond Road
US - 18013 - Bangor, PA
USA

Contact:
Telefon: +1 610 498 4474
Fax: +1 610 498 2602
E-Mail:
info@fiberlanellc.com

Description

- **Application:** Consistent winding of drive cables in greenhouse shading systems
- **Material:** Impact-resistant plastic for extended durability
- **Capacity:** Winding length of 570 cm
- **Installation:** Can be retrofitted onto the drive shaft
- **Feature:** Two-piece design with hose clamp connection
- **Suitable for:** Drive shafts with a diameter of 63 mm

Cable drum for 63 mm shaft – type III provides clean and uniform winding of drive cables in shading systems, thanks to its pre-grooved plastic surface. This design prevents cable overlaps and friction, ensuring a smooth and reliable motion path.

The two-part drum can be retrofitted to the drive shaft without dismantling existing components. The shell halves are joined with a hose clamp and secured to the shaft using a set screw for a stable, vibration-resistant hold.

Made from tough, impact-resistant plastic, the drum protects the cable and increases its service life. Suitable for use with drive cables up to 3 mm in diameter.